

SWEFOG

ATMOSPHERIC HAZERS - ULTIMATE SERIES

Our flagship series. Setting the industry standard since 1998. Current series is the 4th generation Ultimate. Main features:

Instant ON, no warm-up time. Continuous operation. Very high output, extremely low fluid consumption: 0,05 ltr/hour at continuous operation. A 5L canister lasts appr. 80 hrs. Full DMX control with auto-store of last setting used. New air filter system prevents housing from dust. Designed for Swefog Ultimate mineral oil-based fluids.

| Vare nr. | Beskrivelse: | Pris: |
|------------|--|----------|
| 20 202-240 | ULTIMATE 2000 ULTIMATE 2000 DMX 230V 50 Hz | 24.250,- |
| 30 203-240 | ULTIMATE 3000 ULTIMATE 3000 DMX 230V 50 Hz | 32.350,- |
| | <i>Included: AC- connection cable 0,5m and hoses 0,5m & 10m, to connect compressor and haze unit</i> | |
| | ACCESSORIES - ULTIMATE SERIES | |
| 30 016-10 | EXTENSION TUBE 16m/10mm for Ultimate 3000 | 1.465,- |
| 30 025-10 | EXTENSION TUBE 25m/10mm for Ultimate 3000 | 2.190,- |
| | <i>All tubes are compatible with Ultimate III and 300</i> | |

WATER BASED SMOKE PROCESSORS - LIVE SERIES

Extremely high output, 1,800 cubic metres/min. Advanced RISC microprocessor control with alpha-numerical display. Output is set in 99 steps, 1-100%. Silent soft start or immediate burst. Integrated control for an external fan (max 500W) makes T26 Evo2 suitable for use as a powerful outdoor smoke / haze generator. Full DMX control, 0-10V, on-board manual control, intelligent real-time timer & connection for optional manual remote control. Wireless optical fluid sensor. Aluminium cap with metal quick connector & filtered canister air inlet with checkvalve. 2,600W stainless steel heat exchanger. Continuous operation at 50% and elow. Operates up to 2 min at 100%. Warm-up time: Appr. 9 minutes. The SSR version uses a 3,200W heat exchanger and offers ppr. 20% higher output at continuous operation. NOTE: Peak output is equal for T26Evo2 & T26Evo2 SSR. Designed for Swefog Neutral-Pro fluids

| Vare nr. | Beskrivelse: | Pris: |
|------------|---|----------|
| 40 110-240 | LIVE T26 Evo2 X-power HD smoke processor 230V 50 Hz 2,600W | 14.550,- |
| | ACCESSORIES - LIVE SERIES | |
| 100 001 | FLYING BRACKET KIT For Live T26, Live T26 Evo2. With aluclamp for 50mm tubes Extruded aluminium profiles, S/S drip tray. Adjustable hang angle | 4.010,- |
| 100 003 | DUCTING ADAPTOR KIT 4" / 102 mm For Live T26, T26 Evo2. Stainless steel ducting adaptor | 3.935,- |
| 100 002 | MANUAL REMOTE CONTROL UniControl 20 8m cable, 2 channel control (independent for smoke + fan output), DIN connector, smoke ON / OFF control. Hand-held. | 1.540,- |

WATER BASED HAZE GENERATORS - XEON II INTELLHAZER

Water based hazer with high output & precise output control, 1800 W. 7 min heat-up time, continuous operation at all levels. Handles all fluid types in the "Neutral-Pro" series without need of any settings. Optical low fluid sensor. Advanced Sequence Operation Control (A.S.O.C.) programming. Integrated 5L can compartment for high capacity. Designed for Swefoa Neutral-Pro fluids.

| Vare nr. | Beskrivelse: | Pris: |
|------------|-------------------------------------|----------|
| 40 221-230 | XEON II INTELLHAZER DMX 230 V 50 Hz | 14.050,- |

ACCESSORIES - XEON INTELLHAZER SERIES

| | | |
|---------|---|---------|
| 100 002 | MANUAL REMOTE CONTROL UniControl 20 8m cable, 2 channel control (independent for smoke + fan output), DIN connector, smoke ON / OFF control. Hand-held. | 1.540,- |
|---------|---|---------|

ULTIMATE PREMIUM QUALITY OIL BASED HAZE FLUID

Medical oil-based fluid. For use in the Ultimate series and other "cracker" hazers using compressed air and oil-based fluid. Compatible with most "cracker" hazers.

| Vare nr. | Beskrivelse: | Pris: |
|----------|---|----------|
| 161 005 | Ultimate C-fluid 5L canister <i>Creates a very light haze with extremely long hang time, 3+ hours</i> | 648,- |
| 161 025 | Ultimate C-fluid 25L canister | 3.125,- |
| 161 210 | Ultimate C-fluid 210L drum | 22.300,- |
| 162 005 | Ultimate C-XL 5L canister <i>Creates extremely light haze with short hang time. Must be mixed with C-fluid to change density and hangtime.</i> | 849,- |
| 162 025 | Ultimate C-XL 25L canister | 4.010,- |
| 162 210 | Ultimate C-XL 210L drum | 28.600,- |

NEUTRAL-PRO PREMIUM QUALITY WATER BASED FLUID

Mixed with pharma (medical grade) quality polyglycols and extra pure de-ionized Swedish water without content of chlorine. In-house UV-disinfected water, destroying 99.99% of harmful microorganisms.

| Vare nr. | Beskrivelse: | Pris: |
|----------|--|---------|
| 111 005 | Neutral-Pro HD Smoke fluid 5L canister <i>Creates a very high density white smoke. Hang time 0,5 - 1,5hrs.</i> | 254,- |
| 111 025 | Neutral-Pro HD Smoke fluid 25L canister | 1.215,- |
| 111 210 | Neutral-Pro HD Smoke fluid 220L plastic drum | 9.390,- |
| 112 005 | Neutral-Pro MD Haze fluid 5L canister <i>Creates a medium density fog. Hang time 0,5 - 1,5hrs.</i> | 254,- |
| 112 025 | Neutral-Pro MD Haze fluid 25L canister | 1.215,- |
| 112 210 | Neutral-Pro MD Haze fluid 220L plastic drum | 9.390,- |
| 113 005 | Neutral-Pro XTR (Extra light) Haze fluid 5L canister <i>Creates a very light, crystal-clear haze. Hang time 0,5 - 1,5hrs.</i> | 254,- |
| 113 025 | Neutral-Pro XTR (Extra Light) Haze fluid 25L canister | 1.215,- |
| 113 210 | Neutral-Pro XTR Haze fluid 220L plastic drum | 9.390,- |



STRATOSPHERE PREMIUM QUALITY OIL BASED FLUID, for neutral gas operated fog generators

For use in Nitrogen or CO2 neutral gas operated fog generators only. NOT for use in any other type of fog generator. Risk of fire or serious personal injury if used in conventional fog generators, or fog generators operated without a neutral gas.

| Vare nr. | Beskrivelse: | Pris: |
|-----------------|---|--------------|
| 163 005 | STRATOSPHERE HydroPower Universal fluid 5L can. | 648,- |
| 163 025 | STRATOSPHERE HydroPower Universal fluid 25L can. | 3.125,- |
| 163 210 | STRATOSPHERE HydroPower Universal fluid 220L drum | 23.350,- |